


GOUPILLES CYLINDRIQUES RECTIFIÉES  
DIN 6325 - ISO 8734 - NFE 27475  
GROUND DOWEL PINS DIN6325 – ISO8734 – NFE27475



② Désignation : Goupilles cylindriques DIN6325 D x L  
Description: Dowel pins DIN6325 DxL



Matière = Acier trempé revenu pour dureté 58-62 HRC  
Material: Steel hardening and tempering for hardness 58-62 HRC

D m6	L																			
1	4	5	6	8	10	12	14	16												
1,5	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30					
2	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	
2,5	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
3		5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
4			6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
5				8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
6					10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
8					10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50
10						14	16	18	20	22	24	26	28	30	32	36	40	45	50	55
12							16	18	20	22	24	26	28	30	32	36	40	45	50	55
14									20		24		28	30	32	36	40	45	50	55
16											24		28	30	32	36	40	45	50	55
18																	40	45	50	55
20																30	32	36	40	45
25																			50	55
30																			50	60

Boîtes assortiments goupilles voir p. 25  
Boxed sets of pins, see p. 25

- SUR DEMANDE** • Dimensions et tolérances spéciales  
ON REQUEST Other tolerances and dimensions
- Matières spéciales  
Special materials