


GOUPILLES CONIQUES À TÉTON FILETÉ
DIN7977 - ISO8737 - NFE27482

EXTERNAL THREADED TAPER PINS DIN7977 – ISO8737 – NFE27482



☒ Goupilles décollétées (non trempées)
 Turned, non-hardened pins

☒ Désignation : Goupilles coniques DIN7977 DxL
 Description: Taper pins DIN7977 DxL



Matière = 9SMnPb28K
 Material: 9SMnPb28K

D h10	M	L												
5	M5	40	45	50	55	60								
6	M6	40	45	50	55	60	65	70	75	85				
8	M8	40	45	50	55	60	65	70	75	85	100			
10	M10			50	55	60	65	70	75	85	100			
12	M12								75	85	100	120	140	
14	M12								75	85	100	120	140	
16	M16								75	85	100	120	140	160
20	M16										100	120	140	160

SUR DEMANDE

ON REQUEST

- NFE27482 (uniquement en réparation car elle n'est plus utilisée en 1^{er} monte)
 NFE27482 (only for repair as it is no longer used in 1st assembly)
- Dimensions et tolérances spéciales
 Other tolerances and dimensions
- Matières spéciales notamment 100Cr6 trempé - rectifié filetage recuit
 ou inox A2 et A4
 Special materials, particularly 100Cr6 tempered-ground, annealed thread or stainless steel A2 and A4